

FAWLCUCOC

TeraSPEED® LC to Unconnectorized, Fiber Pigtail, 0.9 mm Tight Buffer, 12-fiber Kit, Blue - Aqua (1-12)

Construction Materials

| | |
|------------------------|---|
| Fiber Type | TeraSPEED®, zero water peak singlemode fiber (G.652.D, G.657.A1 or G.652.D, G.657.A1 OS2) |
| Total Fibers, quantity | 12 |

Dimensions

| | |
|----------------------|--|
| Cord Length, maximum | 23 ft 7 m |
| Cord Length, minimum | 2 ft 1 m |
| Ordering Note | For lengths greater than 999 ft (304 m), orders must be in meters Minimum length may vary based on cable configuration |

Environmental Specifications

| | |
|-----------------------|--------------------------------------|
| Environmental Space | Plenum |
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |

General Specifications

| | |
|--------------------------------|--------------|
| Construction Type | Pigtail kit |
| Interface, connector A | LC |
| Interface Feature, connector A | Standard |
| Color, connector A | Blue |
| Interface, connector B | Unterminated |

Mechanical Specifications

| | |
|-----------------------------------|---------------------------------|
| Cable Retention Strength, maximum | 1.00 lb @ 0 ° 1.00 lb @ 90 ° |
|-----------------------------------|---------------------------------|

Regulatory Compliance/Certifications

| Agency | Classification |
|-----------------|--|
| RoHS 2011/65/EU | Compliant |
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |



Included Products

X-TB-8W (Product Component—not orderable) — 900µm Tight Buffered Fiber

- CS-8W-TB (Product Component—not orderable) — TeraSPEED® Singlemode Fiber

460125289 (Product Component—not orderable) — Behind The Wall Pre-Radiused LC Connector for 0.9 mm Fiber, single-mode